

Tata Yodha 2.0

The new Tata Yodha 2.0 is a powerful and robust pickup equipped to carry higher payload and offer faster turnaround time with its powerful engine and rugged aggregates. Updated with bold looks and metallic bumper and fender, the Yodha 2.0 features the Tata signature 'Trust Bar' and a stylish grille amongst other functional upgrades. It has redefined the segment with its all-terrain capabilities. With the highest rated payload capacity of 2000kg, Yodha 2.0 ensures higher profitability and more efficient operations.

USPs:

- Highest rated payload of 2000kg in pickup segment
- Reinforced chassis frame
- Highest torque of 250Nm with a flat curve (1000-2500rpm)
- Bold design with 3 piece metallic bumper, stone-guard, metallic fender assembly, stylish grille and Tata signature 'Trust Bar'
- High ground clearance of 210mm and 16" tyres
- Anti-roll bar at the front for stability on gradients and unlevelled roads
- Advanced utility features for higher savings – Eco Mode Switch, Gear Shift Advisor
- Heating, ventilation and air-conditioning as a standard fitment
- Lubricated for life (LFL) aggregates
- Enhanced safety: Side Under-ride Protection Device (SUPD) & Rear Under-ride Protection Device (RUPD)

Key applications: Fruits & vegetables, agriculture products, industrial goods, poultry, fisheries, water bottles, dairy products and construction material.

Technical specifications:

| Tata Yodha 2.0 | |
|--------------------------------|--|
| Engine type | 2.2-litre 4-cylinder BS6 DI engine |
| Max engine output | 73.6kW@3750rpm |
| Max engine Torque | 250Nm@1000-2500rpm |
| Clutch | Single Plate dry Friction type 260 mm Dia |
| Gearbox | GBS-76-5/4.49 mark 2, Synchronesh 5F+1R |
| Steering | Power Steering |
| Front suspension | Semi elliptical leaf springs - 6 leaves |
| Rear suspension | Innovative Two stage Semi-elliptical leaf springs-9 leaves |
| Front brakes | Hydraulic, twin pot Disc Brake |
| Rear brakes | Drum Brake |
| Tyre | 215/75 R 16 Radial |
| External Load body | 2643x1843mm (8.67x6ft) |
| Ground Clearance | 210mm |
| Wheel Base | 3150mm |
| Width | 1860mm |
| Length | 5350mm |
| Height | 1810mm |
| GVW | 3840kg |
| Kerb weight | 1840kg |
| Payload | 2000kg |
| Grade-ability | 30% |
| Seating capacity | D+1 |
| Warranty (Including Driveline) | 3 Years/3 Lakh km |