

**Tata 709g LPT XD**

Crafted exclusively for 4-tyre requirement with longer deck applications and maximum fuel efficiency, the all-new Tata 709g LPT XD has grown on the strong foundation laid down by the 709g LPT and LPT 407 CNG . The future-ready truck caters to all the applications in the LCV (Light Commercial Vehicle) segment with the trusted Tata 3.8-litre SGI CNG BS6 engine and reliable aggregates. This power packed vehicle has upped the ante in terms of improved product and driver packages, enhanced connectivity, grade-ability, lower cost of ownership, making it the most desired CNG based LCV in India. 709g LPT XD with longer load body is the perfect choice for e-commerce, FMCG and general logistics application.

The top feature upgrades of 709g LPT include: improved power, peak and low-end torque, improved GVW and payload, higher grade-ability, newly designed tilt and telescopic power steering, improved air braking system, Banjo Type rear axle, smooth gear transmission and improved suspension strength. In addition, the vehicle is equipped with music system with Blaupunkt speakers, USB fast charging, new seat design with heat resistant Melba fabric, PTO provision and reverse parking assist.

**USP's:**

- Up to 10% better fuel efficiency
- 5 ft<sup>2</sup> more loading area
- Reliable 3.8-litre SGI engine – high reliability, lower maintenance and longer life
- Air brakes – low maintenance, higher reliability and confident driving in all conditions
- Better warranty coverage
- Safe & comfortable LPT cabin with new instrument cluster, music system, comfortable seats with Melba fabric & improved pedal efforts
- Radial tyres for better fuel efficiency and longer life
- Fleet Edge – Tata Motors new-generation telematics
- Grade-ability of 25% - longer flat torque leads to better restart ability, grade-ability and fuel economy

**Applications:** FMCG, market load, e-commerce, industrial goods, white goods, parcel and courier

**Technical Specifications:**

Engine	3.8-litre SGI BS6	Tyre size	8.25R16 - 16PR
Power	85HP @ 2500 rpm	Clutch size (mm)	280
Torque	285Nm @ 1200-1600 rpm	Brakes	Air brake
Gearbox	GBS27, 5 Speed Manual Synchromesh Gearbox (5F, 1R)	Steering	Tilt and Telescopic Power Steering
Frame	200 x 60 x 5	Grade-ability	25%
Loading area (Ft) (lxb)	16Ft X 6.9Ft	Suspension (Front/ Rear)	Front: Semi elliptical leaf spring and 2 no Hydraulic double acting telescopic type shock absorber
Load body options	CAB, HD		Rear: Semi elliptical leaf spring
Ground clearance (Mm)	216	GVW (KG)	7490
TCD (Mtrs)	13.5	Kerb Weight	3850
Cabin	2.2 M LPT Cab	Payload	3640

**PRODUCT NOTE**

Load body dimensions		Overall dimensions	
Load body Length (in mm )	4889	Wheelbase (in mm)	3800
Load body Width (in mm )	2117	Overall Length (in mm)	6893
Load body Height (in mm )	1835	Overall Height (in mm)	2940
Seating Capacity	Driver + 1	Overall Width (in mm)	2255
Warranty	3 years or 3,00,000km, whichever is earlier*		