

Tata Ultra T.16 Cx

Ultra T.16 Cx provides the best-in-class drivability, comfort and real-time tracking of goods to consigner and consignee. The truck is powered by the 3.3-litre new-generation engine developing 155PS of power and 450Nm of torque at wider rpm band of 1500-2200rpm coupled with the GBS 550 6-speed gearbox and 9 R 20 Radial tube tyre which delivers 10% higher fuel economy. The Ultra cabin offers safety and comfort during long operations. Ultra T.16 Cx is available in multiple deck lengths ranging from 17ft to 24ft for varied applications and terrains.

Value features integrated with Ultra T.16 Cx include: new tilt & telescopic power steering, dual mode FE Switch, real walkthrough, crash-tested cabin, mechanically suspended Melba fabric driver seat, front parabolic suspensions with rubber bush, 7mm thick chassis frame, lockable glove box, bottle holder and a foldable arm rest. In addition, the truck is equipped with an advanced, new-gen instrument cluster with features that include average fuel economy, gearshift advisor, DTE and trip setting.

USPs:

- Crash-tested Ultra walk through cabin with SUV like driving comfort
- 3.3-litre new-generation BS6 engine
- GBS 550 mechanical shift 6-speed gearbox
- Strongest 7mm thick chassis in its class with ladder riveted/bolted design
- Clear internal deck length at all wheelbases to increase the loading span
- Fleet Edge – Tata Motors new-generation telematics
- Dual FE mode – heavy and light for optimal fuel economy
- Four load body options – 17ft, 20ft, 22ft & 24ft

Applications: FMCG, fruits & vegetables, e-commerce, parcel & courier, cement, industrial goods, MLO, white goods and reefers

Technical Specifications:

Engine	3.3-litre TCIC BS6 Engine	Steering Type	Tilt & Telescope Power Steering		
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler	Brakes Type	Dual Circuit Full Air S" Cam Brakes With Auto Slack Adjuster & ABS		
Engine Displacement (cc)	3300	Ground Clearance (mm)	245mm		
Power	155Ps @2600rpm	Grade-ability	26%		
Torque	450 Nm @1500-2200rpm	Rear Axle	Single Reduction, Fully floating axle , RA1085 (RAR - 6.83)		
Clutch	Single Plate Dry Friction Type, 330mm	Battery	12 V - 100 Ah		
Gearbox	GBS 550(6F, 1R)	Fuel Tank Capacity (lt)	160L		
Suspension - Front Type	Parabolic Leaf Spring with Hydraulic double acting Telescopic Shock Absorbers	GVW (kg)	16140		
Suspension - Rear Type	Semi Elliptical with Semi Elliptical Aux spring	Long member Size (mm) (LxBxH)	220mm x 60mm x 7mm		
Tyres	9 R 20 - 16PR Radial (FR-2, RR-4, Spare-1)				
Steering Type*	Tilt & Telescope Power Steering (Dia-420)				
Brakes Type	Dual Circuit Full Air S" Cam Brakes With Auto Slack Adjuster & ABS				
Ground Clearance (mm)	245mm				
WB	3920	4530	4920	5300	
TCD (m)	14.5	16.4	17.7	18.9	
Warranty	3 years/ 3 lakh km				
Seating Capacity	D+2				
Deck length (Ft.)	5217mm (17ft)	6170mm (20.2ft)	6800mm (22.3ft)	7430mm (24.4ft)	