

Since its launch in 2005, the legacy brand Tata Ace has created more than 20 lakh entrepreneurs. Tata Motors has extended the Tata Ace range further with the introduction of an all-new Ace HT+, a product that builds on the attributes of lower cost of ownership and reliability of the Ace brand. Ace HT+ brings together the power and efficiency of a turbocharged diesel engine with a longer load body and increased payload capacity. To the customer, this represents a twofold advantage – the operating economics of Tata Ace with power and performance similar to pickups.

Applications: Agri products, pharma and food products, refrigerated transportation, FMCG and FMCD goods, e-commerce, furniture, construction materials, distribution of fruits, vegetables, beverages and water bottles.

Technical Specifications:

Engine	Tata 800cc DICOR, BS6 Phase 2, Direct Injection, Common Rail, Turbocharged, Intercooled, Diesel engine	Dimensions	
Max. Engine Output	26.0 kW @3750rpm	Length	4075 mm
Max. Torque	85 Nm @1750-2750rpm	Width	1500 mm
No. of Gears	5-Forward 1-Reverse	Height	1858 mm
Clutch	Single plate dry friction diaphragm type	Wheelbase	2250 mm
Steering	Mechanical, variable ratio	Front Track	1310 mm
Front Suspension	Parabolic leaf spring	Rear Track	1343 mm
Rear Suspension	Semi - Elliptical leaf spring	Min TCR	4625 mm
Leaf Width	60mm	Ground Clearance	160 mm
Shock Absorber	Hydraulic double acting telescopic type	Cargo Box Dimensions	2520 mm x 1490 mm x 300 mm
Tyres	155 R13 LT 8PR (Tubeless Tyres)	Seating	D+1
Gradeability	36%		
Top speed	80 km/h		
Gross Vehicle Weight	1950kg		
Payload capacity	900kg		
Fuel Tank Capacity	30L		
DEF Tank Capacity	10.5L		